



Lasertack

New Laser Generation

MGL-FN-532/1~1500mW

LD PUMPED ALL-SOLID-STATE GREEN LASER AT 532nm

All solid state 532nm green laser is made features of high output power stability, good beam profile, ultra compact, long lifetime, low cost and easy operating, which is widely used in collimation, laser medical treatment, scientific experiment, optical instrument, etc.




SPECIFICATIONS

Wavelength (nm)	532±1
Operating mode	CW
Output power (mW)	>1, 5, 10, 20, ..., 1500
Power stability (rms, over 4 hours)	<1%, <3%, <5%
Transverse mode	TEM ₀₀
M ² factor	<1.2
Beam diameter at the aperture (1/e ² , mm)	~2.0
Beam divergence, full angle (mrad)	<1.5
Beam height from base plate (mm)	27.4
Polarization ratio	>100:1 Horizontal±5 degree (Vertical Optional)
Warm-up time (minutes)	<10
Pointing stability after warm-up (mrad)	<0.05
Operating temperature (°C)	10~35
Power supply (90~264VAC)	PSU-H-LED PSU-H-FDA
Modulation option	TTL on/off, 1Hz~1KHz, 1KHz~10KHz, 10KHz~30KHz; and Analog modulation option
Expected lifetime (hours)	10000
Warranty	1 year



Note: The laser head needs to be used on a heat sink with good heat dissipation.

MXL-FN-532




197(L)×70(W)×50(H) mm³, 2.0 kg

PSU-H-LED



277(L)×145(W)×106(H) mm³, 2.6 kg

PSU-H-FDA



236(L)×145(W)×104(H) mm³, 2.3 kg