



# Lasertack New Laser Generation

DPS-1064-B/1~30mJ

## SPECIFICATIONS

### HIGH ENERGY DIODE PUMPED ALL-SOLID-STATE Q-SWITCHED LASER

High energy diode pumped all solid state Q-switched laser at 1064nm has the features of high single pulse energy, short pulse duration, and high peak power, which is widely used in LIBS, LIF, ICP-MS, LCD repair, scientific research, military, and so on.



Wavelength (nm)	1064±1
Operating mode	Q-switched:Electro-optic Modulation
Single pulse energy (mJ)	30
Pulse duration (ns)	<10
Rep. rate (Hz)	1~10, EXT (adjustable)
Energy stability(rms)	<3%
Beam divergence, full angle (mrad)	~1
Beam diameter (mm)	≤3
Warm-up time (minutes)	<15
Beam height from base plate (mm)	35
Cooled method	Air cooled
Operating temperature (°C)	15~30
Power supply (220VAC)	PSU-DPS-B
Expected lifetime (pluses)	10 <sup>9</sup>
Warranty period	1 year



DPS-1064-B	PSU-DPS-B
<p style="text-align: center;">255(L)×85(W)×65(H)mm<sup>3</sup>, 3 kg</p>	<p style="text-align: center;">308(L)×306(W)×106(H) mm<sup>3</sup>, 5.5 kg</p>