



# Lasertack New Laser Generation

MLL-III-543/1~100mW

## LOW NOISE GREEN LASER AT 543 nm

Low noise green laser at 543 nm is made features of ultra compact, long lifetime, low cost and easy operating, which is used in scientific experiment, optical sensor, measurement, instrument, communication, spectrum analysis, etc.



### SPECIFICATIONS

Wavelength (nm)	543±1		
Operating mode	CW		
Output power (mW)	>1, 5, 10, 20, ... , 100		
Power stability (rms, over 4 hours)	<1%, <3%, <5%		
Transverse mode	TEM <sub>00</sub>		
Noise of amplitude (rms, 20Hz~20MHz)	<1%		
M <sup>2</sup> factor	<1.2		
Beam diameter at the aperture 1/e <sup>2</sup> (mm)	~1.2		
Beam divergence, full angle (mrad)	<1.5		
Polarization ratio	>100:1, Horizontal ±5 degree (Vertical Optional)		
Warm-up time (minutes)	<10		
Pointing stability after warm-up (mrad)	<0.05		
Beam height from base plate (mm)	24.8		
Operating temperature (°C)	10~35		
Power supply (90-264VAC or 5VDC)	PSU-III-LED	PSU-III-FDA	PSU-III-OEM-97
Expected lifetime (hours)	10000		
Warranty	1 year		



MxL-III-543	PSU-III-LED	PSU-III-FDA	PSU-III-OEM-97
<p>140.5 (L) × 73 (W) × 46.2 (H) mm<sup>3</sup>, 0.6kg</p>	<p>153 (L) × 155(W) × 92 (H) mm<sup>3</sup>, 1.5kg</p>	<p>133 (L) × 130(W) × 62.2 (H) mm<sup>3</sup>, 1.2kg</p>	<p>94(L) × 75(W) × 49(H) mm<sup>3</sup>, 0.23kg</p>